



■ 20° PRESSURE ANGLE

Fig. 1




Fig. 2






Fig. 3





	Single Thread	Double Thread
Lead	3.148	6.333
Lead Angle	3° 35'	7° 11'

MATERIAL: Steel

WORMS												
Catalog Number	Thread Data				Fig. No.	P.D.	D	d* Bore H8	S	L	D1 Dim.	l Hub Proj.
	Single Thread	Double Thread	Right-Hand	Left-Hand								
A 1C 5MYK10RA	•		•		1	16	18	8	25	—	—	—
A 1C 5MWK10RA		•										
A 1C 5MYK10LA	•			•								
A 1C 5MWK10LA		•			2	16	18	6	22	32	15.7	10
A 1C 5MYK10RB	•		•									
A 1C 5MWK10RB		•										
A 1C 5MYK10LB	•			•	3	16	18	—	25	100	13** (h8)	—
A 1C 5MWK10LB		•										
A 1C 5MYK10RC	•		•									
A 1C 5MWK10RC		•			3	16	18	—	25	100	13** (h8)	—
A 1C 5MYK10LC	•			•								
A 1C 5MWK10LC		•										

*Bore Tolerance: 6 mm + 0.018
8 mm + 0.022

**Shaft Tolerance: 13 mm - 0.027



MATERIAL: Acetal with Brass Insert

WORM GEARS - RIGHT-HAND ONLY						
Catalog Number	No. of Teeth	P.D.	D	D1 Hub Dia.	Thread	
A 1Z 6MWK10R020R	20	20	23	16	Double	
A 1Z 6MYK10R020R	20	20	23	16	Single	
A 1Z 6MYK10R030R	30	30	33	20	Single	

*Tolerance for this bore is + 0.018 (H8).

